

# WIZARD™

# Safety Specs™

## Bifocal Safety Glasses



### Adjustable Fit

### Three Lens Tints and Five Diopters To Choose From

The Wizard Safety Specs are the most significant advancement in the field of safety glasses to date. These Bifocal Safety Glasses provide uncorrected vision in the upper viewing field, and correction for presbyopia (lacking ability to focus on nearby objects) in the reading segments. With fully adjustable ear stems, and available in a range of bifocal powers, fit and comfort are assured. There is no need to wear reading glasses underneath your safety glasses ever again. The ANSI Z87.1-2003 compliant polycarbonate lenses also include UV protection.



- Safety Specs are available in the following bifocal powers: +1.0, +1.5, +2.0, +2.5 and +3.0
- Temples adjust in four different lengths and have panoramic angle adjustment for perfect fit
- Integrated side shields
- 99.9% UV protection up to 380 nm
- Stylish, comfortable, can be worn at all times in the shop
- Helps prevent accidents and mistakes by improving vision
- For anyone who wears reading glasses and works in a shop

Lens Color	Diopter	Stock #
Clear	+1.0	73610
Clear	+1.5	73615
Clear	+2.0	73620
Clear	+2.5	73625
Clear	+3.0	73630

For wholesale orders or dealer inquiries contact us:

Wizard Industries, Inc.

15500 Erwin Street, #1049, Van Nuys, California 91411

Toll Free: 888-346-3826

Phone: 818-781-8033 Fax: 818-781-8106

info@shopspecs.com

<http://www.ShopSpecs.com>

**Dimensions:** Length 8 5/8"; Width 2 1/2"; Height 1 1/2"

**Color/s:** Black with clear lenses

**Packaging Type:** Poly Bag With Header Card

**Package Dimensions:**

Height 10.5"; Width 5"; Thickness 1 7/8"; Weight 1.3 Oz.

**Master Carton:** 144 units, 19 x 11 x 17 inches 11.2 pounds.

**Carton:** 12 units, 12 x 8 x 4 inches 1.7 pounds.

**Magnifications Available:** +1.0, +1.5, +2, +2.5, +3.0

**Construction:** High-impact, optically clear Polycarbonate lenses with UV protection, impact resistant plastic frame and temple pieces.

**Adjustability:** Temple pieces extend in 4 lengths, and adjust for angle

**Compliance:** Complies with ANSI Z87.1-2003, as well as CE-166 and AS/NZS 1337:1992.